



DC POWER TRANSDUCER (4-20mA)

PRODUCT DESCRIPTION

PWT series of Power Transducers are designed for the measurements of DC electric power with high linearity and high accuracy. Input Voltage can be selected between DC $\pm 15V$ and AC110V. It is solution for isolating the sensor output and the current carrying conductor.

KEY FEATURES

- Standard 4-20mA output
- Low cost
- High linearity
- High accuracy

SPECIFICATIONS AND PART NUMBERS

POWER INPUT	VOLTAGE SUPPLY	PART NUMBER	VOLTAGE SUPPLY	PART NUMBER
0-10-100V 0-5-10A*	$\pm 15V$	PTD100V/10A-15	110 V/220V	PTD100V/10A-110
0-10-100V 0-50-200A*	$\pm 15V$	PTD100V/200A-15	110 V/220V	PTD100V/200A-110
0-100-500V 0-200-1000A*	$\pm 15V$	PTD500V/1000A-15	110V/220V	PTD500V/1000A-110
0-500-1000V 0-1000-5000A*	$\pm 15V$	PTD1000V/5000A-15	110V/220V	PTD1000V/5000A-110

*Current sensors (CS series) will be used together for these models.

- Output: 4-20mA standard output
- Linearity: 1% FS
- Frequency: DC
- Load: 6V
- Temperature: $-20^{\circ}C - 70^{\circ}C$
- Isolation: 3000V, 1 minute



DIMENSIONS

80×90×145 or 90 (mm³)

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.